

## DIRECTIONS:

**Surface Preparation:** Concrete must be at least 28 days old before **Crete Seal 25** can be applied. Scrub floor thoroughly with a good detergent or neutral cleaner such as Detco's **Kwik Mop**. Rinse well with clear water and allow to dry thoroughly.

**Application Procedure:** Apply a thin, even coat of finish with a rayon mop or microfiber applicator. (It may also be sprayed with a coarse sprayer, but be mindful of foaming.) Allow at least 30 minutes of dry time. 2 to 3 coats are recommended for optimum performance. No buffing is required, but if the floor is to be buffed, wait at least 48 hours.

Typical coverage is 1,000 - 1,200 sq. ft. per gallon. Application rate will vary depending on surface and application method.

**Maintenance:** Sweep or damp mop every day to remove surface dirt. When damp mopping, use a neutral cleaner such as Detco's **Kwik Mop**.

# Crete Seal 25

## High Gloss Concrete Sealer

**25% Solids**  
**Alkali Resistant**  
**Long Wearing**  
**Inside or Outside Use**  
**Machine Scrubbable**

CAUTION  
KEEP OUT OF REACH OF CHILDREN  
Net Contents: 5 gal (18.93 L)

**Crete Seal 25** seals and protects concrete, brick, terrazzo, and most other non-resilient floor surfaces. It provides a high gloss finish that is machine scrubbable. Sealed floors are water resistant and easy to maintain. This will protect outside surfaces from harsh weather and help prevent the formation of cracks and spalls.

Multiple coats give a magnificent depth of gloss that does not yellow with age.

**PROTECT FROM FREEZING**

0320-005



**CAUTION**  
**KEEP OUT OF REACH OF CHILDREN**  
Dispose of contents/container in accordance with local/regional/national/international regulations.

**INGREDIENTS (CAS#):** Water (7732-18-5), Acrylic Polymers (Trade Secret), Diethylene Glycol Ethyl Ether (111-90-0), Ethylene Glycol (107-21-1)

  
**Detco Industries, Inc.**  
Conway, AR  
1-800-282-2133  
[www.detco.com](http://www.detco.com)